



SINCE 1949

# COAST COUNTIES TRUCK & EQUIPMENT CO.

DBA: COAST COUNTIES PETERBILT

MAIN OFFICE  
1740 N. 4TH, SAN JOSE CA 95112  
P.O. BOX 757, SAN JOSE, CA 95106  
PHONE (408) 453-5510 FAX (408) 453-7637

www.coastcounties.com



June 12, 2025  
Efrain Lopez  
Monterey Regen  
14201 Del Monte  
Marina, CA 93933

Dear Efrain,

Thank you for your recent interest in Coast Counties Truck & Equipment and our line of Peterbilt conventional trucks. In accordance to Sourcewell (formerly NJPA) Contract 060920-PMC, we are pleased to provide our proposal for (1) 2026 model year Peterbilt 537 CNG lube truck for your consideration. **PRICE PENDING AVAILABILITY OF CARB BUILD SLOTS**

## 2026 Peterbilt 537 CNG 33K GVW Chassis

Total Peterbilt List Price	\$188,486.00
15.0% Sourcewell Contract Discount	<\$28,273.00>
Sourcewell Price for Peterbilt 537 Chassis	\$160,213.00

## Sourced Items

McLellan Fuel and Lube Truck	\$236,699.00
Agility CNG System	\$34,542.00
Custom Frame Layout	\$1,500.00
DMV Doc Fee	\$85.00
Tariff Surcharge	\$3,700.00
Extra Pre Delivery Inspection	\$2,000.00
Truck Detail	\$500.00
Freight from McLellan	\$1,100.00*
Flooring Plan Cost	\$8,610.00*
CA Tire Tax	\$10.50*
Sales Tax @8.75%	\$38,433.41

<b>Total Sourced Items (includes sales tax)</b>	<b>\$327,179.91</b>
<b>Total Delivered Price</b>	<b>\$487,392.91</b>

\*Items not subject to sales tax

FOB COAST COUNTIES PETERBILT, SALINAS, CA

Thanks again for considering Coast Counties Truck and Equipment under the Sourcewell Contract, and please let me know if I can be of further assistance.

Sincerely,

  
Dane Lamanna

# McLELLAN INDUSTRIES

# QUOTE

<b>South San Francisco - Sales</b> 251 Shaw Road South San Francisco, CA 94080 650 438 2561 650 438 2561 FAX: 650-589-7398	<b>Hanford - Manufacturing</b> 13221 Crown Avenue Hanford, CA 93230
----------------------------------------------------------------------------------------------------------------------------------------	---------------------------------------------------------------------------

<b>Bill To:</b> Coast Counties P.O Box 757 San Jose, CA 95106  <b>Attn:</b> DANE LAMANNA <b>Tel:</b> 831 801 8403 <b>Fax:</b> <b>Date:</b> JUNE 5,2025	<b>Ship To:</b> MRWMD (Monterey Regional Waste Mangmnt Dist.  <b>FOB:</b> Hanford, CA <b>Quote #</b> <b>Cell:</b> <b>Saleman:</b> JOE DEBATTISTA 650 438 2561
-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------	------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Standard Features Included			
Item	Part #	Description	
*		1000 SINGLE MEDIUM LUBE	INCLUDED
A:	LT100100	LUBE TANK, 1000 / 1 COMPARTMENT	INCLUDED
	SSUN101100	20" D.O.T. LID	INCLUDED
	MT800114	MAIN TANK FITTINGS	INCLUDED
B:	(2) MB100318	BOX, FILTER/TOOL, 48X24X24 ALUM D/P WITH GUTTER	INCLUDED
C:	LT300199	HYDRAULIC SYSTEM (OIL GEAR) (RIGHT HAND)	INCLUDED
D:	LT400152	I.C.C. / DOT LIGHTS (STOP/TAIL/TURN)(ALL LED)	INCLUDED
E:	LT400154	CONTROL PANEL / INSIDE CAB CONTROLS	INCLUDED
F:	MT800113	INTERNAL SAFETY VALVE FUEL SHUTOFF, AIR OPERATED, NC	INCLUDED
G:	MATCH CAB	PAINT, ACRYLIC ENAMEL (BODY ONLY)	INCLUDED
H:	MT500149	HOLD DOWN, LUBE TANK, OFF HIGHWAY	INCLUDED
I:	MT500147	HOLD DOWN, CROSS TANK, OFF HIGHWAY	INCLUDED
J:	MB400118	SAFETY KIT, (BACK-UP ALARM, FIRE EXTINGUISHER, REFLECTOR KIT, NONSKID, SAFETY CLIP RAIL)	INCLUDED
K:	LT200574	CROSS TANK ASSY, NEW CLASSIC, "K" BACK WITH LADDER (MUD FLAPS (2) 24"X24" (2) 36"X24"	INCLUDED
	LT600109	AIR MANIFOLD ASSEMBLY	INCLUDED
	LT300166	HYDRAULIC MANIFOLD ASSY	INCLUDED
L:	LT700203	OIL DEL SYSTEM, (4) McLELLAN HYD OIL PUMPS SPRING REWIND HOSE REELS 1/2"X50' HOSE	INCLUDED
M:	LT700121	GREASE DEL SYSTEM (AIR PUMP 75:1 McLELLAN HYD REEL 3/8"X90' HOSE)	INCLUDED
N:	LT700122	AIR DEL SYSTEM (HYD DRIVEN LE7-10 McLELLAN SPRING REEL 3/8"X50' HOSE)	INCLUDED
O:	LT700123	WATER / COOLANT DEL SYSTEM (120 GAL DUAL TANK, PUMP, REEL, HOSE)	INCLUDED
P:	LT700124	FUEL DEL SYSTEM (McLELLAN 1.25"X50' HOSE, NOZZLE, BLACKMER PUMP, M5 METER)	INCLUDED
Q:	LSP-151-8R	SIGHT GAUGES (5-OIL PRODUCT TANK, 1-HYDRAULIC TANK, 2-WASTE OIL)	INCLUDED
R:	LT700125	WASTE OIL (1" AIR DIAPHRAM PUMP, McLELLAN SPRING REEL, 1"x35' HOSE BALL VALVE, NOZZLE)	INCLUDED
S:	MB100227	FILTER DRAIN BOX	INCLUDED
T:	MB400119	WORK LIGHTS, QUARTZ HALOGEN FLOOD (SET OF SIX)	INCLUDED
U:	LT400131	STROBE LIGHT (AMBER) X-TANK MOUNTED	INCLUDED
V:	MB600102	DRIVE LINE	INCLUDED
W:	PER JOB	HOT SHIFT PTO	INCLUDED
X:	PART OF K	MUD FLAPS (2) 24" X 24" (2) 24" X 36"	INCLUDED

Options in addition to standard features			
Item:	Part #	Description	
1.)	<(-1) LT700203 >	DELETE OIL DELIVERY SYSTEM (MCL. HYD. OIL PUMP, MCL. SPRING REWIND REEL, 1-1/2X50', NOZZLE)	DELETE
2.)	CUSTOMER SUPPLY	INSTALL CUSTOMER SUPPLIED MEGATRAK 9000 FUEL MONITORING SYSTEM	INCLUDED
3.)	<MB100318>	DELETE PASSENGER SIDE TOOL BOX	DELETE
4.)	<MB100227>	DELETE FILTER DRAIN BOX	DELETE
5.)	CUSTOMER SUPPLY	INSTALL NORMALLY CLOSED 1-1/2" SOLENOID VALVE (PLUMB VALVE BEFORE FUEL METER AFTER FUEL PUMP)	INCLUDED
6.)	<LT700119>	DELETE M5 FUEL METER	DELETE
7.)	LT700138	HIGH PRESSURE WASH (HYD. PACE PUMP, 3/8" X 50' SPRING REEL, PLUMB TO L-TANK TO	TBD
8.)	*9011.5	INSTALL 1-1/2" SERIES 900 FILL RITE FUEL METER (LEADS FROM PULSAR TO BE WIRED TO FUEL MONITORING SYSTEM BY CUSTOMER)	INCLUDED
9	DEF SYSTEM	40-60 DEF PLASTIC TANK DIAPH. SYSTEM WITH 50' HOSE AND REEL	INCLUDED
10	DOOR	ALUM DIAMOND PLATE POLISHED SWING UP DOOR AND POWER PRESSURE SYSTEM	INCLUDED

YEAR	MAKE	Chassis Information	
THIS WOULD BE FOR CUSTOMER INFORMATION OR WHAT WE ARE SELLING IF APPLICABLE			

Accepted by:

McLellan Equipment:

Company Representative

Joe DeBattista  
Company Representative



Coast Counties Truck (C505)  
920 Elvee Drive  
Salinas, California 93901

Monterey Regional Waste Mgmt  
14201 Del Monte Blvd  
Marina, California 93933  
United States of America

Dane Lamanna  
Cell Phone:  
Office Phone: (831)758-2441  
Email: dlamanna@coastcounties.com

Efrain Lopez

## Vehicle Summary

Unit		Chassis	
Model:	Model 537	Fr Axle Load (lbs):	12000
Type:	Full Truck	Rr Axle Load (lbs):	21000
Description 1:	537 33k CNG Lube Truck	G.C.W. (lbs):	33000
Description 2:	Fuel Lube 537		
Application		Road Conditions:	
Intended Serv.:	Tanker, Liquid Bulk	Class A (Highway)	100
Commodity:	Other Commodity	Class B (Hwy/Mtn)	0
		Class C (Off-Hwy)	0
		Class D (Off-Road)	0
Body		Maximum Grade:	6
Type:	Tank	Wheelbase (in):	197
Length (ft):	24	Overhang (in):	90
Height (ft):	13.5	Fr Axle to BOC (in):	69.5
Max Laden Weight (lbs):	1000		
		Cab to Axle (in):	127.5
Trailer		Cab to EOF (in):	217.5
No. of Trailer Axles:	0	Overall Comb. Length (in):	327
Type:			
Length (ft):	0	Special Req.	
Height (ft):	0		
Kingpin Inset (in):	0		
Corner Radius (in):	0		
Restrictions			
Length (ft):	40		
Width (in):	102		
Height (ft):	13.5		

Approved by: \_\_\_\_\_

Date: \_\_\_\_\_

Note: All sales are F.O.B. designated plant of manufacture.

Price Level: January 1, 2025  
Deal: 537 33k CNG Lube Truck  
Printed On: 6/13/2025 3:18:40 PM

100% Complete

Date: June 13, 2025  
Quote Number: QUO-1185744-B3R3S0



Sales Code	Std/ Opt	Description	Weight
<b>Base Model</b>			
0005371	S	<b>Model 537</b> The Peterbilt Model 537 is highly versatile to take on the big jobs. It is available as a Class 7 truck or tractor with a GVW up to 33,000 lbs. With a full range of suspensions and an available all-wheel-drive configuration, the 537 is the perfect match for applications such as wrecker, tanker, beverage delivery, and municipal utilities just about any job you can throw at it.	9,870
0091200	S	<b>Other Commodity</b>	0
0093020	O	<b>Tanker, Liquid Bulk</b> General freight (linehaul) service using a liquid bulk tanker body or tanker trailer.	0
0095150	O	<b>Tank</b>	0
0098010	O	<b>California Registry</b> California Registry Required for all vehicles that will be registered in the State of California.	0
<b>Configuration</b>			
0200670	O	<b>Agility Natural Gas Fuel System</b> Assembler - Fontana, CA	0
<b>Frame &amp; Equipment</b>			
0515010	O	<b>10-5/8" Steel Rails 326-384"</b> 10.625 x 3.45 x .313 Dimension, 1,776,000 RBM; Yield Strength: 120,000 psi. Section Modulus: 14.8 cubic inches. Weight: 1.44 lbs/inch pair	257
0611300	O	<b>Heavy Duty 5-Piece Crossmember BOC IPO Standard</b> Class 5, 6, 7	20
0611330	O	<b>Zinc Coated Anti Corrosion Treated Frame Rails</b> Requires Frame Rail Code. Zinc Phosphate coating will replace the standard frame rail primer and provide added corrosion prevention for your customer's operating in severe conditions or in climates where vehicle rust is common.	2
0611790	O	<b>Aluminum Frame Rail Crossmembers</b> Excludes suspension	-7
0612230	O	<b>Custom Wheelbase or Overhang</b> Engineering approval may be required.	0
0613095	O	<b>3-Piece Suspension Crossmembers</b>	0
0620500	O	<b>Frame Components Bolted IPO Huck Fastened</b>	0
0644090	S	<b>EOF Square without Crossmember</b> End-of-frame square without crossmember. For use with body builder installed crossmember.	0
0651090	S	<b>Omit Rear Mudflaps and Hangers</b>	0





Sales Code	Std/Opt	Description	Weight
<b>Front Axle &amp; Equipment</b>			
1011875	O	<b>Dana Spicer E1202IL 12,000 lb, 3.5 in. Drop</b> Axle is designed for applications with a gross axle weight rating (GAWR) of 12,000 lb. The axles have exclusive one-piece forged design knuckle including steer arm, tie rod arm and spindle. This feature helps in greater durability and reduced maintenance.	0
1111190	O	<b>Taper Leaf Springs, Shocks 12,000 lb</b> Hendrickson taper leaf springs, shocks for 12,000 lbs.	169
1243040	S	<b>Power Steering Sheppard HD94</b> Sheppard HD94 power steering gear is a light weight version of heavy duty line-haul power steering gear. For use with 10,000 to 13,200 lb. axle ratings.	0
1250180	O	<b>Power Steering Reservoir Frame Mounted</b> The power steering reservoir is a steering system that eases drivability by applying hydraulic pressure to the steering gear.	0
1353540	O	<b>PHP10 Aluminum PreSet PLUS Hubs</b> PHP10 aluminum PreSet PLUS hubs have a fully integrated spindle nut design, an optimized wheel spacer, magnetic fill plug on drive and trailer hubs for inspection of metal particles in lubricant, with a long life oil seal and bearings are pre-adjusted. Use with Front Axle.	-18
1380070	O	<b>Greasable Front Spring Pins</b>	0
1380240	O	<b>Dana Spicer Wide Track IPO Standard</b> Dana Spicer wide track front axles offer added stability and deliver greater turn angles. 71in KPI IPO 69in for E1202, E1322, E1462, D2000F front axles.	15
1380260	S	<b>Bendix Air Cam Front Drum Brakes 16.5x5</b> For use with 10,000 lbs to 14,600 lbs steer axles. Includes automatic slack adjusters & outboard mounted brake drums.	0
1391410	S	<b>Gusseted Cam Brackets, Steer Axle</b>	0
<b>Rear Axle &amp; Equipment</b>			
1513270	O	<b>Dana Spicer S21-172 Single Axle, 21000 lb</b>	94
1616290	O	<b>PHP10 Aluminum PreSet PLUS Hubs</b>	0
1680420	O	<b>X30 Brake Drums IPO Standard, Drive Axle(s)</b>	-80
1680490	O	<b>Gusseted Cam Brackets, Drive Axle(s)</b>	2
1680500	S	<b>SBM Valve</b> Full trucks require a spring brake modulation (SBM) system for emergency braking application. This system requires an SBM valve and a relay valve with spring brakes on the rear axles. The SBM valve allows the foot valve to operate the rear axle spring brakes if a failure exists in the rear air system.	0
1680550	O	<b>Upsize Parking Brakes</b>	0

Price Level: January 1, 2025  
Deal: 537 33k CNG Lube Truck  
Printed On: 6/13/2025 3:18:40 PM

100% Complete

Date: June 13, 2025  
Quote Number: QUO-1185744-B3R3S0



Sales Code	Std/Opt	Description	Weight
1680795	O	Diff Lock, Single Drive Axle with Speed Interlock	30
1680950	S	Stability System Not Selected Or Not Available	0
1682430	S	Anti-Lock Braking System (ABS) 4S4M ABS-6. Includes air braking system.	0
1684200	S	Synthetic Axle Lubricant All Axles Peterbilt heavy duty models include Fuel Efficient Cognis EMGARD FE75W-90 which provides customers performance advantages over current synthetic lubricants with reduced gear wear and extended maintenance intervals, resulting in increased uptime. In addition, the lubricant provides improved fluid flow to protect gears in extreme cold conditions and withstand the stress from high temperatures, extending component life.	0
1687010	S	Bendix Air Cam Rear Drum Brakes 16.5x7 Bendix Air Cam Rear Drum Brakes to fit all heavy haul, construction, refuse and highway truck and tractor applications. Includes Automatic Slack Adjusters & Outboard Mounted Brake Drums.	0
1688110	O	Heavy Duty Cam Bushings, Drive Axle(s)	0
1705380	O	Ratio 5.38 Rear Axle	0
1816020	O	Reyco 79KB Multi Leaf 23,000 Lb	-35
1911280	O	Reyco Helper Springs 3,000 lb For use with Reyco 79KB suspension	60
1920380	O	Heavy-Duty Shock Absorbers - Reyco 102/79KB Single Drive Suspension Only	30

### Engine & Equipment

2056319	O	L9N 300@2100 GOV@2200 860@1300 (2024 Emissions) N21430 N201 0....Reserve Speed Limit Offset ( N21410 N202 0....Maximum Cycle Distance (N202 N21400 N203 252...Reserve Speed Function Reset N21320 N205 120...Standard Maximum Speed Limit N21420 N206 0....Maximum Active Distance (N20 N21470 P062 NO....Cruise Control Auto Resume ( N21480 P068 NO....Auto Engine Brake in Cruise N21450 P026 NO....Gear Down Protection (P026) N21440 P015 NO....Engine Protection Shutdown ( N21340 P112 93....Hard Maximum Speed Limit (P1 N21350 P001 64....Maximum Accelerator Pedal Ve N21370 P059 64....Maximum Cruise Speed (P059) N21590 P230 YES...Enable Hot Ambient Automatic N21530 P233 YES...Enable Impending Shutdown Wa N21540 P234 60....Timer For Impending Shutdown N21460 P046 1400..Max PTO Speed (P046) N21520 P030 5....Timer Setting (P030) N21570 P031 NO....Idle Shutdown Manual Overrul	475
---------	---	-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	-----

Price Level: January 1, 2025

100% Complete

Date: June 13, 2025

Deal: 537 33k CNG Lube Truck

Quote Number: QUO-1185744-B3R3S0

Printed On: 6/13/2025 3:18:40 PM





Sales Code	Std/Opt	Description	Weight
		N21610 P172 40....Low Ambient Temperature Thre	
		N21630 P171 80....High Ambient Temperature Thr	
		N21550 P516 100....Engine Load Threshold (P516)	
		N21510 P520 YES...Enable Idle Shutdown Park Br	
		N21620 P173 60....Intermediate Ambient Tempera	
		N21330 N207 0.....Expiration Distance (N207)	
		N21500 N209 0.....Expiration Distance (N209)	
2091120	S	<b>EMUX Electronics Architecture</b>	0
2091305	O	<b>Engine Idle Shutdown Timer Enabled</b>	0
2091315	O	<b>Enable EIST Ambient Temp Overrule</b>	0
2091372		<b>Eff EIST NA Expiration Miles</b>	0
2091640		<b>Effective VSL Setting NA</b>	0
2092014	O	<b>Typical Operating Speed 65 MPH</b>	0
2092032	O	<b>Powertrain Optimized for Performance</b> Best analysis for vehicles used in vocational applications or with heavy GCWRs.	0
2140150	O	<b>Remote PTO and Throttle Provision</b> 12-pin connector on engine harness.	0
2140220	O	<b>CARB and EPA Engine Idling Not Required</b>	0
2140460	S	<b>Remote PTO/Throttle, 12-Pin, 250K BOC/BOS</b> J1939, Remote Control Provision	0
2140660	O	<b>CARB Emission Warranty</b>	0
2513060	S	<b>PACCAR 160 Amp Alternator, Brushed</b> PACCAR 160 AMP alternator, brushed producing 160 Amps at road speed and 100 Amps at idle.	0
2522110	O	<b>PACCAR 12V Starter, N/A PACCAR MX Engines</b> PACCAR 12-volt electrical system. With centralized power distribution incorporating plug-in style relays. Circuit protection for serviceability, 12-volt light system w/circuit protection circuits number & color coded.	0
2538040	O	<b>3 PACCAR Premium 12V Dual Purpose Batt 2190 CCA</b> Threaded stud type terminal. Stranded copper battery cables are double aught (00) or larger to reduce resistance.	62
2539410	O	<b>Battery Jumper Terminal Mounted Under Hood</b> LH Frame Rail. Not available with PX-7 engines.	4
2539720	O	<b>Low Voltage Disconnect System</b>	0
2539840	O	<b>MD - Battery Disconnect Switch</b> Mounted on Battery Box	9
2621000	O	<b>2-Speed Fan Clutch For Frequent Start/Stops</b>	0

Price Level: January 1, 2025

100% Complete

Date: June 13, 2025

Deal: 537 33K CNG Lube Truck

Quote Number: QUO-1185744-B3R3S0

Printed On: 6/13/2025 3:18:40 PM



Sales Code	Std/ Opt	Description	Weight
		A 2-speed fan clutch is ideal for vocational applications where the fan clutch engagement time exceeds 10% of the engine run time. When the fan clutch is disengaged, the fan still rotates at 15-25% of the engine RPM. This fan rotation provides crucial airflow to the engine and draws virtually no horsepower.	
2723210	S	<b>18.7 CFM Air Compressor</b> N/A X15. Furnished on engine. Teflon lined stainless steel braided compressor discharge line.	0
2921170	O	<b>Spin-On Fuel/Water Separator for Natural Gas Engines</b>	0
2921210	S	<b>No Fluid Heat Option for Fuel Filter</b>	0
2921310	S	<b>No Electric Heat Option for Fuel Filter</b>	0
3114270	S	<b>High Efficiency Cooling System</b> Cooling module is a combination of steel and aluminum components, with aluminum connections to maximize performance and cooling capability. Silicone radiator & heater hoses enhance value, durability, & reliability. Constant tension band clamps reduce leaks. Chevron Delo Extended Life Coolant (NOAT) extends maintenance intervals reducing maintenance costs. Anti-freeze effective to -30 degrees F helps protect the engine. Low coolant level sensor warns of low coolant condition to prevent engine damage. Radiator Size by Model: 520 1202 sq in, 579 1456.9 sq in, 535/536/537/548 949.3 sq in, 537/548 VOC 1000.3 sq in, 567 1379 sq in.	0
3211140	S	<b>(1) Air Cleaner Engine Mounted</b>	0
3365420	O	<b>Exhaust Single RH Side of Cab</b> Includes RH/UC Catalyst, L9N or ISX12N. Side-of-cab standpipe with the right-hand under cab catalyst box.	-117
3381770	O	<b>Curved Tip Standpipe(s)</b>	1
3387870	O	<b>24" Ht, 5" Dia Chrome, Clear Coat Standpipe(s)</b>	0
<b>Transmission &amp; Equipment</b>			
4052920	O	<b>Allison 3000 RDS-P Transmission, Gen 6</b> Rugged Duty Series	459
4210080	O	<b>1710 HD Driveline, 1 Midship Bearing</b>	75
4230080	O	<b>PTO F/O Chelsea</b>	0
4233910	O	<b>(1) Dash Mounted Single Acting EOH PTO Control</b> Electric-over-hydraulic, spec'ing PTO switch does not ensure the PTO will fit. Sends signal to Allison to engage PTO.	1
4240020	O	<b>Automatic Transmission Oil Cooler</b> Vocational Hood Only	13
4252890	O	<b>Allison FuelSense Not Desired</b> Dynamic Shift Sensing	0

Price Level: January 1, 2025  
Deal: 537 33k CNG Lube Truck  
Printed On: 6/13/2025 3:18:40 PM

100% Complete

Date: June 13, 2025  
Quote Number: QUO-1185744-B3R3S0





Sales Code	Std/Opt	Description	Weight
4252940	O	<b>Allison Neutral At Stop</b> Neutral at Stop features and benefits: Reduces or eliminates the load on the engine when vehicle is stopped, can help lower fuel consumption and CO2 emissions, and is included in FuelSense 2.0 Plus and Max packages only.	0
4256640	O	<b>Allison 6-Speed Configuration, Close Ratio Gears</b> 3000 Series Transmissions.	0
4256920	O	<b>Dash Mounted Push Button Shifter</b> Available with Allison transmissions	3
4257110	O	<b>LH Mounted Trans PTO Provisions</b>	0
4257120	O	<b>RH Mounted Trans PTO Provisions</b>	0
<b>Air &amp; Trailer Equipment</b>			
4510190	S	<b>Bendix AD-HF Air Dryer, Heater</b> Bendix AD-HF air filters protects the life of your engine system and components. Proven PuraGuard oil coalescing technology in the the air dryer cartridge. This oil coalescing filter ensures the removal of oil and oil aerosols before they can contaminate the moisture removing desiccant.	0
4520420	O	<b>Pull Cords All Air Tanks</b>	0
4540420	S	<b>Nylon Chassis Hose</b>	0
4543340	O	<b>Aluminum Painted Air Tanks</b> All air tanks are aluminum with painted finish except when Code 4543330 Polish Aluminum Air Tanks is also selected (then exposed air tanks outside the frame rails will be polished aluminum). Peterbilt will determine the optimal size and location of required air tanks. Narratives requesting a specific air tank size or location will not be accepted for factory installation. See ECAT to determine number or location of air tanks installed.	-45
4611930	O	<b>Body Connections 5' BOC</b> Junction box contains light and power circuits for body connections located 5' from back-of-cab	4
4615250	O	<b>Fitting For F/O Air Port</b> The furnished by owner fitting air port is mounted outboard of the driver's seat. This allows operators access to pressurize truck air, to maintain clean air in the cab.	0
<b>Tires &amp; Wheels</b>			
5069620	O	<b>FF: BR 16ply 11R22.5 R268 Ecopia</b> Efficiency Rating: Poor R268 tread is not a Line Haul tire and is only for Pickup and Delivery or Regional use. Diameter = 41.5 inches; SLR = 19.3 inches	18
5156580	O	<b>RR: MN 16ply 11R22.5 X Works D</b>	120

Price Level: January 1, 2025  
Deal: 537 33k CNG Lube Truck  
Printed On: 6/13/2025 3:18:40 PM

100% Complete

Date: June 13, 2025  
Quote Number: QUO-1185744-B3R3S0



Sales Code	Std/Opt	Description	Weight
5190004	O	<b>Code-rear Tire Qty 04</b>	0
5220410	O	<b>FF: Alcoa 885657 22.5X8.25 High Polish</b> Aluminum wheel severe service.	-28
5320410	O	<b>RR: Alcoa 885657 22.5X8.25 High Polish</b> Aluminum wheel severe service.	-56
5390004	O	<b>Code-rear Rim Qty 04</b>	0
<b>Fuel Tanks</b>			
5532010	O	<b>No Fuel Tank/Fuel System Provided, CNG Only</b>	0
5653070	O	<b>CNG / LNG Frame Rail Mounted Tank Only</b>	0
5653180	O	<b>CNG Fuel System</b> Compressed Natural Gas Fuel System.	0
<b>Battery Box &amp; Bumper</b>			
6020030	S	<b>MD Battery Box, Non-Slip Step LH Under Cab</b>	0
6030630	O	<b>Aluminum Battery Box Cover</b>	4
6030650	O	<b>Diamond Plate Cover For DPF/SCR Box</b>	5
6040550	O	<b>Aftertreatment Aluminum Non-Slip Cab Entry</b> Aftertreatment right-hand under cab step. DPF/SCR for diesel engines, catalyst for natural gas engines. On Models 579 specifying chassis fairings, the box is aerodynamic.	0
6112840	O	<b>Steel Bumper Tapered Chromed</b> Two tow points. ***Warning*** Due to a new legal regulations, all New Medium Duty trucks require headlights to be located in the bumper when the chassis height is GREATER than the following chassis height:  Measurement to bottom of frame at front of frame: for the 107 Aero Hood 32.6, for the 109 Aero Hood 31.4, for the 109 Vocational Hood 26.7. Work with applications if your chassis height is unacceptable.	115
<b>Cab &amp; Equipment</b>			
6510170	O	<b>109" Fepto Hood w/Stationary Grille, 3pc Metton</b>	15
6540160	O	<b>Thermal Insulation Package in Cab</b> The thermal insulation package is designed to make the cab thermally efficient in extreme temperatures. The model 520 adds insulation surrounding the doghouse to reduce engine heat transmitted to the cab.	2
6800180	O	<b>Hood Crown - Bright Finish ipo Molded Gray</b>	0
6914180	S	<b>Sears Driver Seat</b>	0
6924180	O	<b>Sears Passenger Seat</b>	0

Price Level: January 1, 2025  
Deal: 537 33k CNG Lube Truck  
Printed On: 6/13/2025 3:18:40 PM

100% Complete

Date: June 13, 2025  
Quote Number: QUO-1185744-B3R3S0



<b>Sales Code</b>	<b>Std/ Opt</b>	<b>Description</b>	<b>Weight</b>
6930500	O	<b>Drivers Armrest - RH Only</b>	2
6930590	O	<b>Passenger Armrest - LH only</b> Required with Evolution LX seats, optional with Evolution ST Seats.	2
6930800	O	<b>Black Seat Color IPO Standard Color</b>	0
6939110	S	<b>Toolbox Under Passenger Seat</b> Non-Suspension Seat	0
6939400	S	<b>Air Ride Driver</b>	0
6939430	S	<b>Mid Back Driver</b>	0
6939470	S	<b>Vinyl Driver</b>	0
6939510	S	<b>Non-Air Ride Passenger</b>	0
6939530	O	<b>Mid Back Passenger</b>	0
6939570	S	<b>Vinyl Passenger</b>	0
7000065	O	<b>Metal Interior Door Panel Kick Plates</b>	2
7001520	S	<b>Adjustable Steering Column - Tilt/Telescope</b>	0
7001620	S	<b>Steering Wheel With Peterbilt Logo</b> Steering Wheel with embossed Peterbilt logo over horn button.	0
7036130	O	<b>Probilt Interior Charcoal Gray - Curved Roof</b>	0
7110680	O	<b>Exterior Cab Entry Grabhandle</b> Textured; NFPA compliant. Available on Day Cab specifications only.	0
7210420	O	<b>Dark Window Tint IPO Standard Tint - Day Cab</b>	0
7210540	S	<b>Day Cab Rear Window</b> Day cab rear window flush to back of cab.	0
7210550	S	<b>1-Piece Glass Rear Cab Window Fixed</b>	0
7230060	S	<b>1-Piece Curved Windshield</b>	0
7230360	S	<b>Power Door Locks and Power Window Lifts</b> Standard	0
7322010	S	<b>Combo Fresh Air Heater/Air Conditioner</b> With radiator mounted condenser, dedicated side window defrosters, Bi-Level Heater/Defroster Controls, 54,500 BTU/HR, and silicone heater hoses.	0
7330880	O	<b>Additional Fine Particulate Filter For HVAC Syst</b> 3 micron filtration. For use in extreme high dust applications. Not available with Ember filter 7330890.	1

Price Level: January 1, 2025  
Deal: 537 33k CNG Lube Truck  
Printed On: 6/13/2025 3:18:40 PM

100% Complete

Date: June 13, 2025  
Quote Number: QUO-1185744-B3R3S0





<b>Sales Code</b>	<b>Std/ Opt</b>	<b>Description</b>	<b>Weight</b>
7410040	O	<b>Outside Sunvisor - Stainless Steel</b> Not available with 2.1M high roof sleeper.	4
7510060	O	<b>Aero Rear View Mirror Housing, Bright Finish</b>	3
7514010	O	<b>Peterbilt Aero Rear View Mirror, Motorized</b> Includes top mirror with motorized, adjustable dual axis heated glass. Bottom mirror is an integrated convex surface. Includes black textured arms with breakaway feature.	3
7514050	S	<b>Look Down Mirror Over Passenger Door</b> with Black Housing	0
7610500	O	<b>Air Horn Mounted Under Cab</b>	8
7722120	O	<b>ConcertClass, AM/FM, Weatherband, 3.5 Aux</b>	11
7725710	O	<b>Standard Speaker Package For Cab</b> (2) Speakers	4
7728030	O	<b>Radio Mute When In Reverse</b> For automatic or automated transmission	0
7728040	O	<b>Bluetooth Phone and Audio Requires USB Port</b>	0
7728050	O	<b>USB Port</b>	0
7788335	S	<b>Global Telematics Hardware</b>	0
7850015	O	<b>Rear Wall Deep Record/Map Pocket</b>	2
7851480	S	<b>Peterbilt Electric Windshield Wipers</b> With Intermittent Feature.	0
7852020	O	<b>Cab Air Suspension</b>	15
7852050	O	<b>Auto Reset Circuit Protection</b> Daycab and Sleeper	0
7900025	O	<b>Fire Extinguisher, Passenger, Inboard</b> Air seat base, Hazmat approved UL listed/rated ABC	9
7900090	O	<b>Triangle Reflector Kit, Ship Loose</b> Florescent triangle emergency road flares are designed to meet and exceed all DOT standards.	13
7901130	O	<b>Backup Alarm (107 DB)</b>	3
8011850	O	<b>Transmission Oil Temperature (Main)</b> Located in Digital Cluster Display.	0
8021380	S	<b>Air Restriction Indicator</b> Mounted on air cleaner, intake piping, or firewall	0
8021630	O	<b>General Air Pressure 1 Gauge</b> 52mm round, backlit. Physical gauges must be ordered in pairs and are limited to a total of 6.	0
8022160	O	<b>Fuel Filter Restriction Gauge</b>	0

Price Level: January 1, 2025  
Deal: 537 33k CNG Lube Truck  
Printed On: 6/13/2025 3:18:40 PM

100% Complete

Date: June 13, 2025  
Quote Number: QUO-1185744-B3R3S0



Sales Code	Std/Opt	Description	Weight
		52mm Round, backlit. Physical gauges must be ordered in pairs and are limited to a total of 6. If this option is selected on a truck with VMUX electrical architecture, the gauge will be included in the digital display.	
8041200	O	<b>Dual Scale Speedometer MPH Over KPH</b>	0
8070000	O	<b>Disable Brake Light With Engine Brake</b>	0
8070090	O	<b>(3) Additional Dash Switches with Wiring</b> Located on dash panel C. Availability subject to dash space. Includes 4" 14 gauge wire with butt splice at rear of each additional switch.	1
8070810	O	<b>Engine Manifold Pressure (Turbo Boost)</b> Located in Digital Cluster Display	0
8070880	O	<b>Main Instrument Panel (Nat Gas)</b> Digital Cluster 7" Display includes: Physical (Analog) - Speedometer, Tachometer, Oil Pressure, Coolant Temp and Display Gauges - Fuel Level, Volts Telltale, OAT and Primary Air Pressure, Secondary Air Pressure for air brake trucks.	0
8070940	O	<b>Voltmeter Gauge (MD/520 Only)</b> Located in Digital Cluster Display	0
8071470	O	<b>ABS Off-Road Switch</b> Bendix ATC is required on the specification. Off-Road switch allows some wheel slippage prior to ATC activation. Off-Road switch will cause the ATC light to flash, reminding the driver of a condition. Switch should only be used in extreme conditions such as snow, ice or mud.	0
8073050	O	<b>(2) Additional Electric Over Air Switches</b> On/off only, switch has green indicator light, air connections on frame rail under cab. Two accessory solenoid banks with plugs.	2
8111110	S	<b>Headlights Composite Fender Mounted</b> Integral DRL/Park, Turn, and Side Marker	0
8121210	O	<b>(5) Marker Lights, Chrome Housing</b> Aero LED	0
8133470	O	<b>Switch &amp; Wiring for F/O Beacon/Strobe</b> Switch and wiring for furnished by owner beacon / strobe, 10' coiled wire back-of-cab / back-of-sleeper, at rear sill.	2
8133900	O	<b>None Furnished Stop/Tail/Backup Lights</b> Available with full truck only, not available with tractor	-16
8134160	S	<b>Self-Canceling Turn Signal</b>	0
8134180	O	<b>Daytime Running Lights, Mounted In Bumper</b> Driven by chassis height	0
8153050	O	<b>(1) F/O Load Light, Switch, (2) 10' Wire Coils</b> (1) furnished by owner load light, switch, (2) 10" wire coils, under cab/sleeper.	4
<b>Paint</b>			
8500710	O	<b>Standard Paint Color Selection</b>	0
8530770	S	<b>(1) Color Axalta Two Stage - Cab/Hood</b> Base Coat/Clear Coat	0

Price Level: January 1, 2025  
 Deal: 537 33k CNG Lube Truck  
 Printed On: 6/13/2025 3:18:40 PM

100% Complete

Date: June 13, 2025  
 Quote Number: QUO-1185744-B3R3S0



Sales Code	Std/ Opt	Description	Weight
		N85020 A - L0006EY WHITE	
		N85500 CAB ROOF L0006EY WHITE	
		N85300 FENDER L0006EY WHITE	
		N85200 FRAME L0001EA BLACK	
		N85400 HOOD TOP L0006EY WHITE	

### Shipping Destination

### Options Not Subject To Discount

9400091	S	<b>Peterbilt Class 7 Standard Coverage</b> 1 year/Unlimited Miles/km	0
9408528	O	<b>Allison Surcharge 3000 Series Transmission</b>	0
9408626	O	<b>SmartLINQ RD - 5YR Sub</b> Cummins Engines	0
9408703	O	<b>Base Warr: Emissions 5YR/100K MI-EPA Engine</b>	0
9408982	O	<b>Vehicle Layout</b> Option is not subject to discount. Fleets will be split prior to build so that the charge is applied to only one unit. Quotes will not reflect this. <i>Narr NEED 25" CLEAR INSIDE/OUTSIDE RAIL FROM BOC AND CLEAR OUTSIDE FRAME RAILS.</i>	0

### Miscellaneous

9409044	O	<b>109" Stationary Grille Hood (MODEL 537)</b>	0
9409055	O	<b>State Of Registry: California</b>	0
9409645	O	<b>Model Year 2025 Engine</b>	0
9409749	O	<b>2024 Series Emissions Engine</b>	0

### Promotions

### Special Requirements

Special Requirement 1 0098010  
Special Requirement 2  
Special Requirement 3  
Special Requirement 4

### Order Comments

Price Level: January 1, 2025  
Deal: 537 33k CNG Lube Truck  
Printed On: 6/13/2025 3:18:40 PM

100% Complete

Date: June 13, 2025  
Quote Number: QUO-1185744-B3R3S0





Total Weight (lbs)

11,623

Any price increase as the result of force majeure, rising costs of components (including but not limited to material shortages) or government tariffs are not included in the quoted price and will be the financial responsibility of the customer.

## Prices and Specifications Subject to Change Without Notice.

---

Unpublished options may require review/approval.

Dimensional and performance data for unpublished options may vary from that displayed in CRM.

---

### **PRICING DISCLAIMER**

*While we make every effort to maintain the web site to preserve pricing accuracy, prices are subject to change without notice. Although the information in this price list is presented in good faith and believed to be correct at the time of printing, we make no representations or warranties as to the completeness or accuracy of this information. We reserve the right to change, delete or otherwise modify the pricing information which is represented herein without any prior notice. We carefully check pricing specifications, but occasionally errors can occur, therefore we reserve the right to change such prices without notice. We disclaim all liability for any errors or omissions in the materials. In no event will we be responsible for any damages of any nature whatsoever from the reliance upon information from these materials. Please check your order prebills to confirm your pricing information*



**Shipping Destinations**

Intermediate Destination: NONE

Final Destinations	Quantity
--------------------	----------

## Error rendering composition 'Truck-Left'

The operation completed successfully

Dimension	Measurement	Start	End
Axle Spacing	0	197	197
Bumper to Back of Cab	109.5	-40	69.5
Bumper to Front Axle	40	-40	0
Bumper to Front Frame	1.5	-40	-38.5
Cab to End of Frame	217.5	69.5	287
Cab to Rear Axle	127.5	69.5	197
Effective Bumper to Back Of Cab	109.5	-40	69.5
Frame Length	325.5	-38.5	287
Front Axle to Back of Cab	69.5	0	69.5
Front of Frame to Axle	38.5	-38.5	0
Load Space	217.5	69.5	287
Overall Length	327	-40	287
Overhang	90	197	287
Pusher Offset #1	0	197	197
Pusher Offset #2	0	197	197
Pusher Offset #3	0	197	197
Tag Offset	0	197	197
Wheelbase	197	0	197



Error rendering composition 'Truck-Top'

The operation completed successfully

**Note:** The image displayed is representative only. It should not be construed as a layout diagram.  
Dimensions and components are not to scale.

Selected Options (Wheelbase: 197)

Sales Code	Description	Length	Side
6040550	Aftertreatment Aluminum Non-Slip Cab Entry	45.3	Right
5532010	No Fuel Tank/Fuel System Provided, CNG Only	0	??
6020030	MD Battery Box, Non-Slip Step LH Under Cab	27.6	Left